## **Specifications (UAP)**

UniFi AP	
Dimensions	20 x 20 x 3.65 cm
Weight	290 g (430 g with Mounting Kits
Networking Interface	(1) 10/100 Ethernet Por
Buttons	Rese
Antennas	2 Integrated (Supports 2x2 MIMO with Spatial Diversity
Wi-Fi Standards	802.11 b/g/n
Power Method	Passive Power over Ethernet (12-24V
Power Supply	24V, 0.5A PoE Adapter Include
Maximum Power Consumption	41
Max TX Power	20 dBn
BSSID	Up to Four Per Radio
Power Save	Supported
Wireless Security	WEP, WPA-PSK, WPA-TKII WPA2 AES, 802.11
Certifications	CE, FCC, I
Mounting	Wall/Ceiling (Kits Included
Operating Temperature	-10 to 70°C (14 to 158° F
Operating Humidity	5 - 80% Condensin


VLAN	802.1Q
Advanced QoS	Per-User Rate Limiting
Guest Traffic Isolation	Supported
WMM	Voice, Video, Best Effort, and Background
Concurrent Clients	100+
Supported Data Rates (Mbps)	
Standards	Data Rates
802.11n	6.5 Mbps to 300 Mbps (MCS0 - MCS15, HT 20/40)
802.11b	1, 2, 5.5, 11 Mbps

6, 9, 12, 18, 24, 36, 48, 54 Mbps

\* 2.4 GHz



802.11g



www.ubnt.com/unifi